

## DoP.BM02.21-0001

## **DECLARATION OF PERFORMANCE**

The Vault, Dakota Drive, Estuary Commerce Park

Speke, Liverpool, L24 8RJ

Unique identification code of the product type	Intended use	Systems of AVCP	Approved body	Harmonised standard
MDF.H 1mm to >12mm	Laminate flooring intended for internal use as non-structural	3	1066	EN 14041:2018

The unique identification code of the product-type is a combination of the technical class, product type and products nominal thickness.

Essential characteristics	Performance	Pictogram
<sup>1</sup> Content of pentachlorophenol (PCP)	≤ 5ppm	
Emission of formaldehyde	E1	<b>Е1</b> НСНО
<sup>2</sup> Reaction to fire min. thickness 6.5mm	Cfl-s1	C <sub>II</sub> -s1
<sup>3</sup> Slipperiness (slip resistance)	DS, μ≥ 0.3	OS DS
Water tightness	N/A	
Durability of reaction to fire	N/A	
Electrical behaviour	N/A	

<sup>1</sup> No raw material used would contain PCP

The performance of the product identified is in conformity with the declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Mr. John Roberts, Quality Assurance Manager

Date 30/11/2021 at the Vault, Dakota Drive, Estuary Commerce Park

<sup>2</sup> Floor covering loose laid over any wood based substrate  $\geq$  D-s2, d0, tested according to EN 13501-1:2010 for direct end use application as floor covering for interior use on a mineral subfloor, using adhesive or not.

<sup>3</sup> Tested according to EN 13893:2002 (dry conditions)